

BEST AVAILABLE COPY

Utility Patent
Ser. No. 10/752,625

AMENDMENTS TO THE CLAIMS

Please amend the claims below by deleting items with a strikeout (i.e. ~~patent~~) or brackets / double brackets(i.e., [patent] or [[patent]]) and adding items with an underline (i.e. patent).

1. Canceled.

2. Canceled.

3. Canceled.

4. Canceled.

5. Canceled.

6. (Currently Amendment) [[The]] A telescopically adjustable support brace [[of Claim 5]] comprising:
a linearly elongated crossbar terminating at opposing ends, wherein said crossbar comprises a first
crossbar and a second crossbar pivotally coupled about pivot means, wherein said pivot means further
comprises a lock and wherein said lock comprises an elongated body having a head terminus and an
opposing tail terminus, said head terminus includes a downwardly extending projection, and said tail
terminus affixed to one of said first crossbar and said second crossbar;

a pair of adjustable arms, wherein each one of said pair of arms is inserted into one of said ends, said
pair of arms telescopically adjustable therein;

and

a pair of cleats, wherein each one of said cleats is distally affixed to one of said pair of arms;
wherein said pair of arms are adjustably set at a fixed linear length for maintaining a fixed linear distance

BEST AVAILABLE COPY

Utility Patent
Ser. No. 10/752,625

between two objects.

7. (Original) The brace of Claim 6, wherein said projection is insertable into a cavity formed on one of said first crossbar or said second crossbar opposite said tail terminus, said projection and said cavity coupled to maintain horizontal integrity in said brace.

8. (Original) The brace of Claim 6, wherein said lock further comprises a retention member formed on an anterior surface of said lock, said retention member comprising an orifice for receiving a wire.

9. (Original) The brace of Claim 8, wherein upward urging of said wire disengages said projection from said cavity, thereby releasing said first crossbar and said second crossbar to pivot about said pivot means and permit extraction of said brace.

10. (Original) The brace of Claim 6, wherein said lock further comprises a guard encompassing said lock, a interstice provided between said guard and said lock so as to permit upward urging of said lock by a retention member and a corresponding wire passed therethrough, said guard preventing hyper extension of said lock and thereby preventing damage or failure to said lock.

BEST AVAILABLE COPY

Utility Patent
Ser. No. 10/752,625

11. (Currently Amended) The brace of Claim 2, wherein said pivot means comprises a pivot bolt.
12. (Currently Amended) The brace of Claim ~~[[1]]~~ 6, wherein apertures are formed in said crossbar and said pair of arms, said apertures on said crossbar aligned with said apertures on said pair of arms and receiving a pin therethrough to impinge at a fixed linear length.
13. (Original) The brace of Claim 12, wherein said apertures are spaced at approximately one inch intervals.
14. (Currently Amended) The brace of Claim ~~[[1]]~~ 6, wherein each one of said pair of cleats is threadably adjustable to achieve fine adjustment of a linear length of said brace.
15. (Currently Amended) The brace of Claim ~~[[1]]~~ 6, wherein each one of said pair of cleats alternately comprises a plurality of points and a plurality of recesses intermediate thereto.
16. (Original) The brace of Claim 16, wherein said plurality of points are provided to enhance resistance against inward collapse of said two objects.
17. (Currently Amended) The brace of Claim ~~[[1]]~~ 6, wherein said brace is easily disassembled after use

BEST AVAILABLE COPY

Utility Patent
Ser. No. 10/752,625

so as to remove excess concrete accumulated therein.

18. (New) The brace of Claim 6, wherein displacement of said ends permits extraction of said brace from between said two objects.